

SKÄRVÄTSKA 155500200

Last changed: 23/04/2012 Internal No: 155500200

1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name / designation SKÄRVÄTSKA 155500200

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.3 Details of the supplier of the safety data sheet

NATIONAL MANUFACTURER/IMPORTER

Enterprise Luna Verktyg & Maskin AB
Postal code SE-441 80 ALINGSÅS

Country SVERIGE

Telephone + 46 322 60 60 00 **Fax** + 46 322 60 64 43

CONTACT PERSONS

Name	E-mail	Telephone	Country
Jörgen Bengtsson		+ 46 322 60 64 52	

2 Hazards identification

2.1 Classification of the substance or mixture

DPD Classification: Xi; R36/38

CLP Classification: Skin Irrit. 2H315, Eye Dam. 1H318

Most important HSE hazard effects: Causes skin irritation. Causes serious eye damage.

2.2 Label elements



Signal word: None

EC-Label: No

COMPOSITION

Borsyra, förening med 2-aminoetanol (15 - 15 %), POLYOXYETYLENOLEYLETERFOSFAT (1 - 5 %), POLY(OXIETEN)OLEAMID (1 - 5 %), N,N $^{\prime}$ -METYLENBISMORFOLIN (1 - 5 %), 3-jod-2-propynyl butylkarbamat (0,1 - 1 %), 2-(2-Butoxietoxi)etanol (1 - 3 %), N-alkylerad bensotriazol (0,1 - 0,3 %), Petroleum oil, highly refined (DMSO-EXTRAKT<3% IP346) (\sim 80 %)

H Statements

H315 Causes skin irritation.
H318 Causes serious eye damage.

P Statements

P262 Do not get in eyes, on skin, or on clothing.

P305/351/338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P337/313 If eye irritation persists: Get medical advice/attention.



SKÄRVÄTSKA 155500200

Last changed: 23/04/2012 Internal No: 155500200

SUPPLEMENTAL HAZARD INFORMATION (EU)

Formaldehyde.

2.3 Other hazards

3 Composition/information on ingredients

3.2 Mixtures

Ingredient name	Reg.No	EC No.	CAS No.	Conc. (wt%)	DPD- Classification	CLP- classification
Borsyra, förening med 2-aminoetanol		247-421-8	26038- 87-9	15 - 15 %	Xi,R36	Eye Irrit. 2 H319
POLYOXYETYLENOLEYLETERFOSFAT		POLYMER	39464- 69-2	1 - 5 %	Xi,R38 - R41	Skin Irrit. 2 H315 Eye Dam. 1 H318
POLY(OXIETEN)OLEAMID		POLYMER	26027- 37-2	1 - 5 %	Xi,R41	Eye Dam. 1 H318
N,N'-METYLENBISMORFOLIN		227-062-3	5625-90- 1	1 - 5 %	Xn,C,R22 - R34 - R52	Acute Tox. 4 H302 Skin Corr. 1B H314 Eye Dam. 1 H318
3-jod-2-propynyl butylkarbamat		259-627-5	55405- 53-2	0,1 - 1 %	Xn,N,R20/22 - R41 - R50	Acute Tox. 4 H302/332 Eye Dam. 1 H318 Aquatic Chronic 1 H410
2-(2-Butoxietoxi)etanol		203-961-6	112-34- 5	1 - 3 %	Xi,R36	Eye Irrit. 2 H319
N-alkylerad bensotriazol		279-501-3	80584- 88-9	0,1 - 0,3 %	Xn,Xi,R22 - R41 - R43 - R52/53	Acute Tox. 4 H302 Eye Dam. 1 H318 Aquatic Chronic 4 H413 Skin Sens. 1A H317
Petroleum oil, highly refined (DMSO-EXTRAKT<3% IP346)				~ 80 %		

Full text of R-, H- and EUH-phrases: see section 16.

The EUH hazard statements mentioned in CLP-classification are only label elements.

4 First aid measures

4.1 Description of first aid measures

INHALATION

Fresh air and rest. Heat. Rinse nose, mouth and throat with water. Consult a doctor if symptoms should occur.

INGESTION

DO NOT INDUCE VOMITING!Contact physician.



SKÄRVÄTSKA 155500200

Last changed: 23/04/2012 Internal No: 155500200

SKIN CONTACT

Wash skin with soap and water. Remove contaminated clothing. Consult a doctor if symptoms should occur. Immediate hospital care if the product has been forced through the skin at high pressure.

EYE CONTACT

Important! Immediately rinse with water for at least 5 minutes. Get medical attention promptly if symptoms occur after washing. Continue rinsing during the journey to the doctor.

4.2 Most important symptoms and effects, both acute and delayed

4.3 Indication of any immediate medical attention and special treatment needed

5 Fire-fighting measures

5.1 Extinguishing media

SUITABLE EXTINGUISHING MEDIA:

Fire may be extinguished using powder, foam or carbon dioxide (CO2).

UNSUITABLE EXTINGUISHING MEDIA

Do not use water.

5.2 Special hazards arising from the substance or mixture

SPECIAL HAZARDS

Vapours may ignite. In the event of a fire, irritating smoke is formed. Carbon monoxide may be formed in the event of incomplete combustion.

5.3 Advice for fire-fighters

ADVICE FOR FIREFIGHTERS

Wear suitable respiratory protection.

OTHER INFORMATION

Only trained personnel may undertake fire fighting in enclosed spaces. Containers close to fire should be removed or cooled with water.

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

PERSONAL PRECAUTIONS

Use personal protective equipment.

6.2 Environmental precautions

ENVIRONMENTAL PRECAUTIONS

Prevent discharges into the sewage system, watercourses or lakes.

6.3 Methods and material for containment and cleaning up

METHODS AND MATERIAL

Bank with sand, earth or other inert absorption agent and collect. Treat as dangerous waste. Immediately inform the authorities if the emission reaches the sewage system and watercourses. Inform the emergency service in the event of major spillage.

6.4 Reference to other sections



SKÄRVÄTSKA 155500200

Last changed: 23/04/2012 Internal No: 155500200

7 Handling and Storage

7.1 Precautions for safe handling

PRECAUTION FOR SAFE HANDLING

Prevent spillage.

7.2 Conditions for safe storage, including any incompatibilities

CONDITION FOR SAFE STORAGE, INCLUDING ANY UNCOMPATIBILITIES

Store above freezing.

7.3 Specific end uses

8 Exposure controls / Personal protection

8.1 Control parameters

OEL value

Ingredient name	CAS no.	Range	ppm	mg/m3	Year	Notification
Petroleum oil, highly refined (DMSO-EXTRAKT<3% IP346)		15 min.		3		
Petroleum oil, highly refined (DMSO-EXTRAKT<3% IP346)		8 h		1		
R=Toxic for reproduction, H=Skin absorption, K=Carcinogenic, A=Sensitising, T=Upper limit, M=Mutagenic						

OTHER INFORMATION REGARDING LIMIT VALUES AND MONITORING

Contains mineral oil for which a threshold value for oil mist must be applied.

8.2 Exposure controls

APPROPRIATE ENGINEERING CONTROLS

Good personal hygiene is important. Use only in well-ventilated areas. Remove contaminated clothing. Do not put polluted rags in your pockets. Use suitable protective gloves and protective clothes if there is risk of direct contact or splashing. Facilities for eye rinsing must be available.

EYE PROTECTION

Use approved safety goggles or face shield.

SKIN PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HAND PROTECTION

Protective gloves (nitrile rubber, fluorocarbon rubber).

9 Physical and chemical Properties

9.1 Information on basic physical and chemical properties

PHYSICAL STATE Liquid.

COLOUR Brownish.

ODOUR Weak. Oil.

SOLUBILITY Soluble in organic solvents

WATER SOLUBILITY Emulsable in water.



SKÄRVÄTSKA 155500200

Last changed: 23/04/2012 Internal No: 155500200

Parameter	Value/unit	Method/reference	Observation
pH consentrate	No data		
pH in solution	~ 9,4		
Melting point	No data		
Freezing point	No data		
Initial boiling point and boiling range	No data		
Flash point	No data		
Evaporation rate	No data		
Flammability (solid, gas)	No data		
Flammability limits	No data		
Explotion limits	No data		
Vapour pressure	No data		
Vapour density	No data		
Relative density	No data		
Partition coefficient	No data		
Auto-ignition temprature	No data		
Decomposition temprature	No data		
Viscosity	~ 88 mm2/s	ASTM D 445 40°C	

9.2 Other safety information

Parameter	Value/unit	Method/reference	Observation
Density	~ 999 kg/m³	ASTM D 4052 15°C	

Note no.	Comments
----------	----------

10 Stability and Reactivity

10.1 Reactivity

10.2 Chemical stability

CHEMICAL STABILITY

Stable under recommended storage and handling conditions.

10.3 Possibility of hazardous reactions

POSSIBILITY OF HAZARDOUS REACTIONS

Strong oxidizing agent.

10.4 Conditions to avoid

10.5 Incompatible materials

10.6 Hazardous decomposition products:

HAZARDOUS DECOMPOSITION PRODUCTS

Formaldehyde. Carbon monoxide may be formed in the event of incomplete combustion.

11 Toxicological information

11.1 Toxicological effects

ACUTE TOXICITY - ORAL

May cause nausea, vomiting, diarrhoea and stomach ache.

SKIN CORROSION/IRRITATION

Irritant. May cause allergies on prolonged or repeated contact with the skin.



SKÄRVÄTSKA 155500200

Last changed: 23/04/2012 Internal No: 155500200

SERIOUS EYE DAMAGE/IRRITATION

Irritant

RESPIRATORY OR SKIN SENSITISATION

May cause allergy. May cause hypersensitivity.

OTHER TOXICOLOGICAL INFORMATION

Protracted or repeated contact in combination with poor hygiene may cause skin problems in the form of skin inflammation (dermatitis), eczema and oil acne. Used oils may contain contaminants hazardous to health.

12 Ecological information

12.1 Toxicity

ACUTE AQUATIC TEST RESULTS

Forms an oil film on water surfaces that may harm aquatic organisms and may disturb the transport of oxygen at the air/water interface.

ECOTOXICITY

Low toxicity to aquatic organisms.

12.2 Persistence and degradability

DEGRADABILITY

The principal constituents are expected to be biodegradable. Slowly biodegradable.

12.3 Bioaccumulative potential

SKÄRVÄTSKA 155500200				
Test	Exposure time	Value/unit	Species	Source
Log Pow		> 3		

Contains component/components that can be bioaccumulated.

12.4 Mobility in soil

MOBILITY

Emulsable in water.

12.5 Results of PBT and vPvB assessment

12.6 Other adverse effects

13 Disposal considerations

13.1 Waste treatment methods

GENERAL REGULATIONS

Dump or destroy in accordance with official recommendations and applicable legislation.

14 Transport information

Classified as Dangerous Goods:

No



••	••		
CVAD	/ATCVA	15550020	n
JAAR	VAI3RA	ー・コココいいとい	

Last changed: 23/04/2012 Internal No: 155500200

Land transport (ADR/RID) 14.1 UN-No. 14.4 Packing Not applicable. Not applicable. group 14.2 Proper Not applicable. 14.5 Not applicable. Shipping Environmental Name hazards Not applicable. 14.3 Class(es) Hazard Not applicable. label(s) Hazard ID: Not applicable. Not applicable. Tunnel restriction

Inland water ways transport (ADN) 14.4 Packing 14.1 UN-No. Not applicable Not applicable. group 14.2 Proper Not applicable. 14.5 Not applicable. Shipping Environmental Name hazards 14.3 Class(es) Not applicable. Enviromentally Not applicable. hazardous in tank-vessels

code

Sea transport (IMDG) 14.1 UN-No. 14.4 Packing Not applicable. Not applicable. group 14.2 Proper Not applicable. 14.5 Not applicable. Shipping **Environmental** Name hazards 14.3 Not applicable. Class(es) Sub Risk: Not applicable. IMDG Code Not applicable. segregation group Marine Not applicable. pollutant EMS: Not applicable

Air transport (ICAO-TI / IATA-DGR) 14.1 UN-No. Not applicable. 14.4 Packing Not applicable. group 14.2 Proper 14.5 Not applicable. Not applicable. Shipping Environmental Name hazards 14.3 Not applicable. Class(es) Hazard Not applicable label(s)

15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2 Chemical Safety Assessment

16 Other information



SKÄRVÄTSKA 155500200

Last changed: 23/04/2012 Internal No: 155500200

LIST OF R	ELEVANT R-PHRASES
R20/22	Harmful by inhalation and if swallowed.
R22	Harmful if swallowed.
R34	Causes burns.
R36	Irritating to eyes.
R36/38	Irritating to eyes and skin.
R38	Irritating to skin.
R41	Risk of serious damage to eyes.
R43	May cause sensitisation by skin contact.
R50	Very toxic to aquatic organisms.
R52	Harmful to aquatic organisms.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

LIST OF R	ELEVANT H-STATEMENTS
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H410	Very toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
H302/332	Harmful if swallowed or if inhaled.