

MACHINE TYPE:

ANGLE GRINDER for boards 115 and 125 mm: Up to 1100W. For boards 180 and 230 mm: Up to 2200W.

ANGLE GRINDER for boards 115 and 125 mm: Over 1100W. For boards 180 and 230 mm: Over 2200W.

BATTERY MACHINE

STRAIGHT MACHINE

PETROL DRIVEN & STATIONARY

Material thickness	Rec. Board thickness
2 mm	0.8 mm
3 mm	1.0 mm
5 mm	1.3 mm
7 mm	1.6 mm
10 mm	2.0 mm
over 10 mm	2.5 mm

For optimal results, see the table to select the correct thickness.
This gives the fastest cutting and minimal material loss.

	QUANTUM	BLUE FIRE	ACCU	ACCU 1-2-3	NORTON 1-2-3	NORLINE	X-TREME LIFE	OIL & GAS	NORZON QUICK CUT	BDX	BDX STONE	GEMINI
	+++++				++++				+++		++	
STEEL, STRUCTURAL STEEL	o	o	o	o	*	o	o	o	o	o		*
LOW ALLOY STEEL	o	o	o	o	*	o	o	o	o	o		*
HIGH ALLOY STEEL	o	o	o	o	*	o	o	o	o	o		*
SHEET METAL, SECTIONS	o	o	o	o	*	o	o	*	o			*
STAINLESS STEEL, INOX	o	o	o	o	*	o	o	o	o	o		
CAST IRON	o					o	*		o		*	
NON-FERROUS METALS				o		o					*	
TITANIUM						o					*	
STONE, CONCRETE			o	o		o					o	
GLAZED TILES, CERAMICS			o									
GLASS, PLASTIC			o	o							*	

o = Strongly recommended

* = Recommended