

RÖRTRÅD RC KX-706M 202630083

Last changed: 13/06/2012 Internal No: 202630083

1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name / designation RÖRTRÅD RC KX-706M 202630083

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.3 Details of the supplier of the safety data sheet

NATIONAL MANUFACTURER/IMPORTER

Enterprise Luna Verktyg & Maskin AB
Postal code SE-441 80 ALINGSÅS

Country SVERIGE

Telephone + 46 322 60 60 00 **Fax** + 46 322 60 64 43

CONTACT PERSONS

Name	E-mail	Telephone	Country
Jörgen Bengtsson		+ 46 322 60 64 52	

2 Hazards identification

2.1 Classification of the substance or mixture

DPD Classification: Carc. Cat. 3; R40, R43, Xn; R48

CLP Classification: Skin Sens. 1BH317, Carc. 2H351, STOT RE 2H373

Most important HSE May cause an allergic skin reaction. Suspected of causing cancer. May cause damage to

hazard effects: organs through prolonged or repeated exposure.

2.2 Label elements



Signal word: None

EC-Label: No

COMPOSITION

Järn (80 - 98 %), Manganese (1,1 - 1,95 %), Koppar (0,01 - 0,04 %), Kisel (0,45 - 0,92 %), Krom (0,01 - 0,19 %), Nickel. (0,01 - 0,03 %), Molybden (0,01 - 0,33 %), Titan (0,05 - 0,22 %)

H Statements
III Statements

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

2.3 Other hazards

3 Composition/information on ingredients



RÖRTRÅD RC KX-706M 202630083

Last changed: 13/06/2012 Internal No: 202630083

3.2 Mixtures

Ingredient name	Reg.No	EC No.	CAS No.	Conc. (wt%)	DPD-Classification	CLP-classification
Järn			7439-89-6	80 - 98 %		
Manganese			7439-96-5	1,1 - 1,95 %	Xn,R48	STOT RE 2 H373
Koppar		231-159-6	7440-50-8	0,01 - 0,04	N,R50/53	Aquatic Chronic 1 H410
Kisel			7440-21-3	0,45 - 0,92 %		
Krom			7440-47-3	0,01 - 0,19 %		
Nickel.			7440-02-0	0,01 - 0,03 %	Xn,Xi,R40 - R43	Skin Sens. 1 H317 Carc. 2 H351
Molybden			7439-98-7	0,01 - 0,33		
Titan			7440-32-6	0,05 - 0,22 %		

Full text of R-, H- and EUH-phrases: see section 16.

The EUH hazard statements mentioned in CLP-classification are only label elements.

4 First aid measures

4.1 Description of first aid measures

INHALATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

- 4.2 Most important symptoms and effects, both acute and delayed
- 4.3 Indication of any immediate medical attention and special treatment needed
- 5 Fire-fighting measures
- 5.1 Extinguishing media

SUITABLE EXTINGUISHING MEDIA:

All common fire extinguishing agents may be used.

- 5.2 Special hazards arising from the substance or mixture
- 5.3 Advice for fire-fighters
- 6 Accidental release measures
- 6.1 Personal precautions, protective equipment and emergency procedures
- 6.2 Environmental precautions
- 6.3 Methods and material for containment and cleaning up

METHODS AND MATERIAL

See section 13.

6.4 Reference to other sections

7 Handling and Storage



RÖRTRÅD RC KX-706M 202630083

Last changed: 13/06/2012 Internal No: 202630083

7.1 Precautions for safe handling

7.2 Conditions for safe storage, including any incompatibilities

7.3 Specific end uses

8 Exposure controls / Personal protection

8.1 Control parameters

OEL value

Ingredient name	CAS no.	Range	ppm	mg/m3	Year	Notification
Titan	7440-32-6	8 h		13		
Koppar	7440-50-8	15 min.				
Koppar	7440-50-8	8 h		1		
R=Toxic for reproduction, H=Skin absorption, K=Carcinogenic, A=Sensitising, T=Upper limit, M=Mutagenic						

OTHER INFORMATION REGARDING LIMIT VALUES AND MONITORING

Possible reaction products i welding fume Manganese oxide, ozon, nitrogen dioxid

8.2 Exposure controls

APPROPRIATE ENGINEERING CONTROLS

Use only in well-ventilated areas. Avoid contact with skin. Observe normal hygiene such as washing hands before meals, etc.

EYE PROTECTION

Use breathing masks and eye protection when smoke is present.

SKIN PROTECTION

Wear suitable protective clothing. Use a welding helmet during welding

HAND PROTECTION

Wear suitable gloves.

RESPIRATORY PROTECTION

Use breathing masks and eye protection when smoke is present.

OTHER INFORMATION

During welding fumes will be formed The fumecontant is depending on the electrode type and the base material Primarily iron oxid, secondarily complex oxides of manganese may be formed Also ozone and nitrogen dioxide can be formed by arc radiation

9 Physical and chemical Properties

9.1 Information on basic physical and chemical properties

PHYSICAL STATE Electrode



RÖRTRÅD RC KX-706M 202630083

Last changed: 13/06/2012 Internal No: 202630083

Parameter	Value/unit	Method/reference	Observation
pH consentrate	No data		
pH in solution	No data		
Melting point	No data		
Freezing point	No data		
Initial boiling point and boiling range	No data		
Flash point	No data		
Evaporation rate	No data		
Flammability (solid, gas)	No data		
Flammability limits	No data		
Explotion limits	No data		
Vapour pressure	No data		
Vapour density	No data		
Relative density	No data		
Partition coefficient	No data		
Auto-ignition temprature	No data		
Decomposition temprature	No data		
Viscosity	No data		

9.2 Other safety information

Note no.	Comments

10 Stability and Reactivity

10.1 Reactivity

10.2 Chemical stability

10.3 Possibility of hazardous reactions

10.4 Conditions to avoid

CONDITIONS TO AVOID

Strong acids. Strong alkalis.

10.5 Incompatible materials

10.6 Hazardous decomposition products:

11 Toxicological information

11.1 Toxicological effects

ACUTE TOXICITY - DERMAL

May cause sensitisation by skin contact.

CARCINOGENICITY

Some risk of cancer cannot be excluded after frequent exposure.;

12 Ecological information

12.1 Toxicity

ECOTOXICITY

Copper. The product may damage plants and organisms in the ground and water.

12.2 Persistence and degradability



RÖRTRÅD RC KX-706M 202630083

Last changed: 13/06/2012 Internal No: 202630083

12.3 Bioaccumulative potential

12.4 Mobility in soil

12.5 Results of PBT and vPvB assessment

12.6 Other adverse effects

13 Disposal considerations

13.1 Waste treatment methods

GENERAL REGULATIONS

Dump or destroy in accordance with official recommendations and applicable legislation.

14 Transport information

Classified as Dangerous Goods: No

Land transpor	t (ADR/RID)		
14.1 UN-No.	Not applicable.	14.4 Packing group	Not applicable.
14.2 Proper Shipping Name	Not applicable.	14.5 Environmental hazards	Not applicable.
14.3 Class(es)	Not applicable.		
Hazard label(s)	Not applicable.		
Hazard ID:	Not applicable.	Tunnel restriction code	Not applicable.

Inland water wa	ys transport (ADN)			
14.1 UN-No.	Not applicable.	14.4 Packing group	Not applicable.	
14.2 Proper Shipping Name	Not applicable.	14.5 Environmental hazards	Not applicable.	
14.3 Class(es)	Not applicable.			
Enviromentally hazardous in tank-vessels	Not applicable.			

Sea transport	(IMDG)			
14.1 UN-No.	Not applicable.	14.4 Packing group	Not applicable.	
14.2 Proper Shipping Name	Not applicable.	14.5 Environmental hazards	Not applicable.	
14.3 Class(es)	Not applicable.			
Sub Risk:	Not applicable.			
IMDG Code segregation group	Not applicable.			
Marine pollutant	Not applicable.			
EMS:	Not applicable.			



RÖRTRÅD RC KX-706M 202630083

Last changed: 13/06/2012 Internal No: 202630083

Not applicable.

Air transport (ICAO-TI / IATA-DGR)

14.4 Packing 14.1 UN-No. Not applicable. Not applicable.

group 14.2 Proper Not applicable. 14.5

Shipping Environmental Name

hazards

14.3 Not applicable. Class(es)

Hazard Not applicable. label(s)

15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2 Chemical Safety Assessment

16 Other information

LIST	OF	RELEVANT	R-PHRASES

R40 Limited evidence of a carcinogenic effect. R43 May cause sensitisation by skin contact.

R48 Danger of serious damage to health by prolonged exposure.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

LIST OF RELEVANT H-STATEMENTS

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H410 Very toxic to aquatic life with long lasting effects.