

## **Product information**

## 95 26 165

## **Cable Shears**

With opening spring

IEC 60900 DIN EN 60900



**☆1000V /////** 

- For cutting copper and aluminium single conductors as well as multiple stranded cables
- Clean and smooth cut without crushing and deformation
- Not suitable for steel wire and hard drawn copper conductors
- Precision-ground, hardened blades
- Easy cutting with one-hand operation
- With guard
- Adjustable bolted joint, self-retaining screw
- Internal opening spring, protected and captive High-grade special tool steel, forged, oil-hardened

General	
Article No.	95 26 165
EAN	4003773069980
Shears	chrome plated
Handles	insulated with multi-component grips, VDE-tested
weight	275 g
Dimensions	165 x 63 x 26 mm
Standard	DIN EN 60900 IEC 60900
Reach	Nein
RohS	no

Technical details	
Style	2
Cutting capacity copper cable, multiple- stranded	50 mm <sup>2</sup>
Cutting capacity copper cable, multiple- stranded	Ø 15 mm
AWG	1/0
VDE tested	yes

Classification	
eCl@ss 5.1.4	21040601
ETIM 5.0	EC000142
ETIM 6.0	EC000142
proficl@ss 6.0	EAD256c001
UNSPSC 13.1	23241616

technical change and errors excepted

## **KNIPEX** Quality – Made in Germany





Cut performed with a Cable Shear: easy, clean cut without any deformation of the cable





 $95\ 26\ 165$ : Catch locks shears to the opening spring inside

